



## SPECIFICATION

<b>Model NO.</b>	<b>SC-SNY5MPD-W / SC-SNY5MPD-G</b>
<b>Video Output Mode</b>	AHD/TVI: 5MP@20fps/12.5fps, 4MP/2MP@30fps; CVI: 4MP/2MP@30fps
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	5MP
Effective Pixels	5MP:2592*1944 4M:2560*1440
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
S/N Ratio	≥50dB
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	3.6mm Fixed Lens
Pixels	5M Pixels
Auto Iris Support	NO
<b>Night Vision</b>	
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Power On / Off	Smart IR control
<b>Camera Features</b>	
Starlight	/

Day/Night	YES
OSD Menu Language	YES
White Balance	AUTO / MANUAL
Gain Control	AUTO
Noise Reduction	3DNR
Picture Adjustment	YES
WDR	YES
OSD Support	YES
UTC	YES
Dip Switch	/

## General

Housing	Metal, IP66
Bracket	NO
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Audio	/
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	φ93 x 74(H) mm
Weight	400g